

7700 W Olive Ave - Peoria, AZ - 85345 - 407-523-3770 - 407-523-2722

## **ETF-MT Product Specification**

Pre-insulated piping system designed for above ground or direct buried Chilled Water, Hot Water and all other 45° to 250° medium temperature systems.

Carrier Pipe: Schedule 40 A53B ERW Steel.

**Insulation:** Polyurethane foam: K Factor 0.14, Density 2.0 to 3.0 PCF, 90-

95% closed cell conforming to mil spec –1-24172 and ASTM-C-591 completely filling the annular space between carrier pipe

and jacket. Maximum service temperature of 250°

**Jacketing Material:** High Density Polyethylene (HDPE) casing Type III, Category 5,

Class C conforming to ASTM D-1248 or as specified. For

jacket thickness see attached schedule

**End Seal:** Mastic end seals, factory applied to insulation ends.

Insulation of Straight Joints:

Prior to joining carrier pipe an HDPE sleeve is slid onto jacketing on either side of joint. After welding and hydro testing, the HDPE sleeve is slid in place and sealed with heat shrink tape. Polyurethane foam is then mixed and poured into

the annular space and sealed watertight.

**Fittings:** All fittings are field welded and insulated utilizing ETF West

fitting insulation kits. Fitting kits consist of hard shell mitered HDPE matching the thickness of jacket, polyurethane foam

and heat shrink tape.

**Backfilling:** Underground systems shall be buried in a trench of not less

than 24 inches deeper than the top of the pipe jacket and not less than 18 inches wider than the combined O.D. of all piping systems. Backfill should be tamped compactly in place. No rock shall be used in the first foot of the backfill. To meet H-20 highway loadings, there must be 24 inches from top of jacket to

grade of the compacted fill.

7700 W Olive Ave - Peoria, AZ - 85345 - 407-523-3770 - 407-523-2722

Table 1: Specified Carrier Pipe / HDPE Jacket

Nominal Pipe Size	Minimum Insulation Thickness	Nominal Jacket Size	Nominal Jacket Size
1/2"	1.83	4.50	150 mils
3/4"	1.73	4.50	150 mils
1"	1.59	4.50	150 mils
1 1/4"	1.42	4.50	150 mils
1 ½"	2.30	6.63	150 mils
2"	2.13	6.63	150 mils
2 ½"	1.88	6.63	150 mils
3"	1.57	6.63	150 mils
4"	1.80	8.00	175 mils
5"	2.22	10.00	175 mils
6"	1.69	10.00	175 mils
8"	1.90	12.43	175 mils
10"	1.66	14.06	175 mils
12"	1.56	15.87	175 mils
14"	1.92	17.83	200 mils
16"	1.90	19.80	200 mils
18"	1.95	22.17	225 mils
20"	1.85	24.00	250 mils
24"	1.85	28.07	275 mils
30"	2.85	36.00	275 mils

## **ETF WEST LLC WARRANTY**

ETF West LLC warrants its products only to the extent that it will replace those proved to have manufactured defects, within a one-year period from date of delivery. ETF West must be provided an opportunity to inspect an alleged defective product and the installation application. This warranty does not provide for the expenses incurred for removal, re-installation or consequential damages arising from the defective material. There is no warranty other than that described above, and no one is authorized to issue any other warranty related to ETF West LLC products.









